



**EXL
POWER**

Industrial & Automotive lubricants

AP-3 GREASE

LITHIUM BASE GREASE

GREASE / AP-3 GREASE (lithium base grease)

PRODUCT DESCRIPTION

Ap-3 grease is made from lithium complex soaps which have excellent mechanical stability & water tolerance. These can work smoothly under high temperature & pressure for a very long time & have also very good resistance to oil separation during operation.

APPLICATIONS

Long term lubrication of chassis fittings, wheel bearings, grease cups, universal joints of trucks, buses, tractors, earth moving machinery etc. Anti-friction bearings of heavily / shock loaded industrial equipment.

PERFORMANCE LEVEL

- AP-3 GREASE (lithium base grease)

BENEFITS

- Creamy white in colour.
- Provides protection to moving parts under very server shock load conditions.
- Prolongs equipment life.
- Resists water wash out and change in consistency within working range of temperatures.
- Excellent shear stability.
- Extends lubrication intervals.

TYPICAL PROPERTIES

CHARACTERISTICS	AP-3 GREASE
Consistency of the worked grease at 25°C a) At 60 double strokes b) At 10000 double strokes	265 to 295 Shall not be more than 30 units from the consistency at 60 double stroke
Drop Point, °C, Min.	190
Penetration, D217 worked 60xmm/10	235
Thickener	lithium soap

*This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.
Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.*