



**EXL
POWER**

Industrial & Automotive lubricants

NLGI GREASE

SHC - 1500

GREASE / NLGI GREASE (non soap synthetic hydro carbon grease)

PRODUCT DESCRIPTION

It is a non soap high temperature synthetic organo clay base grease with smooth & homogeneous, free from objectionable odour & visible impurities. It possesses good pumpability characteristics, it is free from deleterious materials and fillers.

APPLICATIONS

Recommended for bearing operating at temperature upto 260°C. Recommended for bearing greases and as such this should be used only after complete removal of old one.

PERFORMANCE LEVEL

- NLGI GREASE (non soap synthetic hydro carbon grease)

BENEFITS

- High dropping point
- Excellent water resistance
- High-temperature limitations
- Reduce friction
- Reduces wear & heat
- Reduces maintenance & associated costs
- Reduces noise in bearing Reduce energy consumption.
- Protection against corrosion Extended service life of bearing
- Reduce leakage of grease from bearing

TYPICAL PROPERTIES

CHARACTERISTICS	NLGI GREASE
Consistency of the worked grease at 25°C a) At 60 double strokes b) At 10000 double strokes	220 to 250 does not differ by more than 30 units from the consistency at 60 double stroke
Drop Point, °C, Min.	260
Penetration, D217 worked 60xmm/10	280
Thickener	organo clay

*This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.
Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.*