



**EXL  
POWER**

Industrial & Automotive lubricants

# SUPER QUANTUM DIESEL ENGINE OIL

## DIESEL ENGINE OIL / SUPER QUANTUM 15W40 (API CH-4)

### PRODUCT DESCRIPTION

SUPRE QUANTUM 15W40 is a premium performance, multi-grade, heavy-duty diesel engine oil specifically designed to lubricate a wide range Of diesel engines requiring API CH-4, ACEA E2-96 performance lubricants operating under the most severe service conditions.

### APPLICATIONS

- Mixed fleets of diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated).
- Construction equipment including both old and new equipment.
- Commercial road transport machineries including the latest electronic controlled engines.
- Off-highway vehicles and plant.

### PERFORMANCE LEVEL

- SUPER QUANTUM 15W40 (CH-4, ACEA E2-96)

### BENEFITS

- Exceptional soot handling capability avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.

### TYPICAL PROPERTIES

| CHARACTERISTICS                                 | SUPER QUANTUM 15W40 |
|-------------------------------------------------|---------------------|
| Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s) | 115                 |
| Appearance                                      | Bright Amber        |
| Viscosity Index                                 | 136                 |
| Pour Point (°C)                                 | -21                 |
| Flash Point (°C, COC)                           | 225                 |
| TBN, mg KOH/g, (ASTM 2896)                      | 12                  |

*This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.*  
Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.