

TRACTOR PLUS SAE 20W50

TRACTOR OIL / TRACTOR PLUS 20W50 (API CH4)

PRODUCT DESCRIPTION

Mixed fleets of tractors diesel engines (high-speed, four-stroke naturally aspirated) premium performance, heavy duty and high Density diesel engine oil developed for round the year use to meet the requirements of a wide range of diesel engine of tractors And other farm equipments. Heavy-duty diesel engine oil specifically designed to new generation tractors diesel engines requiring API CH-4/SL, ACEA E2 96 performance lubricants operating under the most severe service conditions. It provide long drain interval (about 500hours) to diesel engines for better long-lasting service.

APPLICATIONS

Tractor plus 20w50 grade is recommended for modern emission compliant trem IIIA engines of all tractors manufacturers. Older tractors (Made on trem ii/iii technology etc.) would also derive performance benefits from this product. The oil can also be used in construction Equipment & dg sets.

PERFORMANCE LEVEL

- TRACTORS PLUS 20W50 (API CH-4/SL, ACEA E2 96)
- TRACTORS DIESEL ENGINES (API CH-4/SL, ACEA E2 96)

BENEFITS

- Exceptional soot handling capability avoiding filter plugging, cylinder head sludge, abrasive polishing wear and oil thickening.
- · Excellent deposit control on valves and piston crown lands reduces oil consumption.
- Exceptional oxidation stability and soot control extends oil drain capability so that equipment is in service longer generating revenue.

TYPICAL PROPERTIES

CHARACTERISTICS	TRACTOR PLUS 20W50
Kinematic Viscosity @ 100°C (cSt)	18
Viscosity Index	125
Pour Point (°C)	-27
Flash Point (°C, COC)	242

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not afecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.

Follow us on: **() ()** ()

Website :www.exlpower.com