



LUBIN PLUS

DIESEL ENGINE OIL

DIESEL ENGINE OIL / LUBIN PLUS 15W40 (API CF-4)

PRODUCT DESCRIPTION

LUBIN PLUS 15W40 is a High performance, multi-grade diesel engine oil specially designed to lubricate a wide range of diesel Engines Requiring API CF-4 performance lubricants.

APPLICATIONS

- Mixed fleets of diesel engines (high-speed, four-stroke, turbo charged or naturally aspirated..
- Commercial road transport.
- Off-highway vehicles and plant.
- Small diesel engines in marine service (e.g. fishing, river transport, etc).
- Generator sets.

PERFORMANCE LEVEL

- LUBIN PLUS 15W40 (API CF-4, ACEA E2-96)

BENEFITS

- Advanced detergent/dispersant additive system maintains power output by providing outstanding deposit control under the high Temperature conditions encountered in turbocharged engines.
- Highly effective detergent additive system minimizes piston crown land deposits which can lead to damaging bore polishing.
- The proven metallo-organic anti-wear additive system reduces wear in severe service by forming a protective layer on all metal contact surfaces.
- The mid-ash, medium dispersancy formulation provides very good overall performance in mixed fleets of different engine designs, allowing Fewer oils to be stored and reducing the chance of problems arising through product misapplication.

TYPICAL PROPERTIES

CHARACTERISTICS	LUBIN PLUS 15W40
Kinematic Viscosity @ 100°C (mm ² /s)	15
Appearance	Bright Amber
Viscosity Index	132
Pour Point (°C)	-21
Flash Point (°C, COC)	225
TBN, mg KOH/g, (ASTM 2896)	10

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.