



EASYCUT-N

Neat Cutting Oil

CUTTING OIL / EASYCUT-N (NEAT CUTTING OIL)

PRODUCT DESCRIPTION

EASYCUT-N is blended from highly purified base oils with fatty oils and chlorinated additives for a wide range Machining operation with good surface finish without discoloration of the work piece, It minimizes the tools from Excessive wear during use

APPLICATIONS

EASYCUT-N is recommended for multipurpose machining operation of ferrous and non ferrous metals including different grinding and milling operations.

PERFORMANCE LEVEL

- EASYCUT-N (Neat Cutting Oil)
- Meets IS: 3065-1985, TYPE I, Grade 2 (RE-AFFIRMD 2002)

BENEFITS

- Highly oxidation stability.
- Prolonged tool life, excellent surface finish, superior cooling and lubricating properties.
- Excellent rust protection.

TYPICAL PROPERTIES

CHARACTERISTICS	EASYCUT-N
Kinematic Viscosity @ 40°C (mm ² /s)	38
Appearance	Amber
Pour Point (°C)	-12
Flash Point (°C, COC)	210
Copper Strip Corrosion for 3 Hrs at 100°C, Max.	1

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.