



**EXL
POWER**

Industrial & Automotive lubricants

POWERPRESS - 100

COMPRESSOR OIL

COMPRESSOR OIL / POWERPRESS - 100, ROTARY & RECIPROCATING AIR COMPRESSOR

PRODUCT DESCRIPTION

Powerpress Grades are manufactured from highly purified base oils with oxidation, rust, corrosion and foam inhibitors. They provide excellent lubrication under high temperature and high load conditions with low carbon-forming tendency and protection against entrained air. Powerpress grades are designed to provide superior thermal and oxidation stability and rust protection.

APPLICATIONS

Powerpress compressors operating up to 220°C air discharge temperature. are recommended for use in the cylinder lubrication of reciprocating and rotary air

PERFORMANCE LEVEL

- POWERPRESS - 100 (Rotary & Reciprocating Air Compressor)
- Meets IS : 13256 - 1992 (RA 2004) Type DAA, DIn 51506 VD L

BENEFITS

- Superior oxidation and high temperature stability
- Improved component cleanliness
- Improved extended service intervals
- Low wear to improve anti-wear and lubricating properties
- Improved ash-less technology
- Excellent performance at high temperature and good start ability in cold temperature

TYPICAL PROPERTIES

CHARACTERISTICS	POWERPRESS - 100
Kinematic Viscosity @ 40°C (mm ² /s)	100
Appearance	Clear, bright, Amber
Pour Point (°C, COC)	-10
Flash Point (°C, COC)	235

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.