



Industrial & Automotive lubricants

HYPO

(HIGH PRESSURE PUMP OIL)

HYPO / HIGH PRESSURE PUMP OIL

PRODUCT DESCRIPTION

HYPO is a premium grade high performance pressure pump oil. HYPO helps the pump for increase much more pressure for better spray results and helps to increase pump work performance. HYPO oils provide extreme lubricity to pump parts for increase life.

APPLICATIONS

HYPO Recommended preferably for non-critical all loss lubrication systems and other applications such as lubrication of bearings, open gears, light loaded slides and guide ways of machine tools. They are also recommended for pump for increase much more pressure for better spray results other applications which do not require additive containing lubricants. These oils can also be used for flushing of inaccessible internal surfaces of various automotive and industrial equipment.

PERFORMANCE LEVEL

- HYPO (High Pressure Pump Oil)

BENEFITS

- HYPO helps the pump for increase much more pressure
- HYPO helps to increase pump work performance
- This performance can help to provide long pressure pump life and low maintenance costs.

TYPICAL PROPERTIES

CHARACTERISTICS	HYPO
Kinematic Viscosity @ 100°C (mm ² /s)	18
Kinematic Viscosity @ 40°C (mm ² /s)	46-49
Viscosity Index	90
Pour Point (°C)	-8
Flash Point (°C, COC)	180

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.