



**EXL
POWER**

Industrial & Automotive lubricants

MAX PLUS 15W40

MULTI-GRADE ENGINE OIL



ENGINE OIL / MULTI-GRADE 15W40

PRODUCT DESCRIPTION

MAX PLUS 15W40 Multi-Grade engine oil blended from high viscosity index base oils. They have good inherent oxidation and thermal stability with excellent ability to separate from water. MAX PLUS 15W40 are specially formulated to improve adhesiveness and film strength characteristics.

APPLICATIONS

MAX PLUS 15W40 Multi-Grade engine oil recommended preferably for non-critical all loss lubrication systems and other applications such as lubrication of bearings, open gears, light loaded slides and guide ways of machine tools. They are also recommended for lubrication of looms in the textile mills and other applications which do not require additive containing lubricants. These oils can also be used for top-up in diesel engine oil chamber or flushing of inaccessible internal surfaces of various automotive and industrial equipment.

PERFORMANCE LEVEL

- Multi-Grade 15W40

BENEFITS

- MAX PLUS 15W40 provides good performance in both two- and four-cycle engines making it a good choice for all applications where ashless and low-ash oils are recommended.
- Its advanced system protects engines against scuffing, scoring and wear particularly during critical break-in periods.
- This performance can help to provide long engine life and low maintenance costs.

TYPICAL PROPERTIES

CHARACTERISTICS	MAX PLUS 15W40
Kinematic Viscosity @ 100°C (mm ² /s)	13
Kinematic Viscosity @ 40°C (mm ² /s)	42-46
Viscosity Index	90
Pour Point (°C)	-6
Flash Point (°C, COC)	178

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.
Produced by PECIFIC PETROLEUM PRODUCTS PVT. LTD.